Split unit air conditioner




Product data sheet

Product category	Split unit air conditioner
Brand	Qlima
Model	S 2251
Colour	White
EAN code	8713508793269
EAN indoor unit	8713508793177
EAN outdoor unit	8713508793238

Technical specifications		Cooling	Heating	
SEER / SCOP	W/W	6,1	4	
Energy efficiency class average season		A++	A+	
PdesignC / PdesignH	kW	5,1	3,8	
Capacities cooling / heating (min./nom./max.)	kW	1,25 / 5,10 / 5,91	1,25 / 5,13 / 6,07	
Power consumption (nom.)	kW	1,578	1,382	
Indicative annual energy consumption during season (Qce / Qhe)	kWh/a	293	1330	
Power supply	V/Hz/Ph	220-240~ / 50 / 1		
Current (max.)	A	13		
Airflow (low/mid/high)	m³/h	620 / 530 / 800		
For rooms up to indoor unit	m³	140 - 185		
Dehumidification capacity	l/24 h	36		
Operating range - indoor unit	°C	17 ~ 32	0 ~ 30	
Operating range - outdoor unit	°C	-15 ~ 53	-20 ~ 30	
Thermostatic range	°C	16~31		
Sound pressure level indoor unit at 1m (SPL)	dB(A)	27		
Sound pressure level outdoor unit at 1m (min.) (SPL)	dB(A)	55		
Fan speeds		5		
Control type		electronic / remote control		
Included filters	type	Screen		
Refrigerant type / GWP / Charge	R/g	R32 / 675 / 1000		
CO₂ equivalent	tonnes	0,675		
Max. length refr. pipe between in- / outdoor unit	m	25		
Max. diff. in height between in-/outdoor unit	m	10		
Diameter gas connection	Ø mm/inch	9.52 (3/8)		
Diameter liquid connection	Ø mm/inch	6.35 (1/4)		
Dimensions indoor unit (w x d x h)	mm	910 x 206 x 294		
Dimensions outdoor unit (w x d x h)	mm	853 x 349 x 602		
Compressor		rotary / GMCC		
Protection class indoor unit	IPxx	IPX0		
Protection class outdoor unit	IPxx	IPX4		
Net. weight - indoor unit	kg	10,0		
Net. weight - outdoor unit	kg	35		
Warranty	year	2		
Warranty compressor	year	4		

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

CE 2.4 YEARS





$W \times D \times H =$

in: 97.9 x 27.7 x 37.2 cm out: 89 x 38.5 x 62.8 cm



Gross weight

in: 13 kg out: 38 kg



Package content

Indoor unit, Outdoor unit, Remote control, Remote control holder, AAA battery (2x), Screen filter, Drainage tube, User manual, Installation manual

Accessories (to order)

Description EAN code

S 2251



Cooling, heating & dehumidifying



Inverter techology



Indoor freezing prevention (8°C)



Eco-friendly refrigerant



Remote control with display included



Timer function



Sleep mode

Split unit air conditioner

Cooling + dehumidifying + heating (heat pump): The air conditioning is a complete year-round air treatment system. It heats and cools in an efficient way and can also be used as a dehumidifier.

Air conditioning: In COOLING mode the unit produces a refreshing cool airflow.

Heating: In HEATING mode the unit produces a warm air flow. The unit absorbs heat from the outdoor air to warm the air inside, a very efficient technique.

Dehumidifying: In DRY mode the unit extract excessive moist from the room. Note: In COOLING mode the air is also dehumidified.

Inverter technology: The DC Inverter air conditioner uses its maximum power to get to the set temperature when the appliance is turned on. Once the tempeature is reached, the unit continuously adjusts the compressor speed to maintain the set temperature.

Minimum energy consumption: The compressor works at minimum capacity once the set temperature is reached. As a result, the over all power consumption is reduced significantly (up to 35% less than non inverter/ conventional types).

Home Freezing prevention: By activating the freezing prevention mode (in heating mode only) the unit overrules the indoor temperature setting and set it to approx 8-10°C. In this mode the unit operates at the lowest possible energy consumption.

Environment friendly refrigerant R32: The most preferred and environmental friendly refrigerant R32 is used in the air conditioner.

Remote control with LCD screen: The air conditioner can be operated by the remote control up to a distance of approx. 8 metres.

Remote control holder: The unit is delivered with a convenient holder that can be mounted on a wall

Adjustable airflow: The up-down airflow can be automatically changed by using the SWING mode. The left-right airflow can be changed manually.

Sleep Mode: The air conditioner increases (cooling) or decreases (heating) automatically the set temperature with 1°C per hour (first two hours) and then maintain the temperature (next five hours). After 7 hours, the unit will stop automatically. In this mode the unit works silently and saves energy at the same time

Fan speed setting: The airconditioner has multiple speed setting. The LCD display on the remote control will show the chosen speed

Automatic operation:In auto mode the unit selects the most suitable operating mode, by monitoring he indoor temperature: Cooling, Dehumidifying or Heating.

Timer: Timer function can be set between 30 minutes and 24 hours (Timer On or Timer Off).