

Model name

AP12RT UA3 (Outdoor unit) / AP12RT NSJ (Indoor unit)

Function (indicate if present)		If the function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.		Declared capacity* for heating / Colder climate, at indoor temperature 20°C and outdoor temperature Tj		Declared Coefficient of performance* / Colder climate, at indoor temperature 20°C and outdoor temperature Tj	
cooling	Y	Tj=-7°C	Pdh	x,x	kW		
heating	Y	Tj=2°C	Pdh	x,x	kW		
		Tj=7°C	Pdh	x,x	kW		
		Tj=12°C	Pdh	x,x	kW		
		Tj=bivalent temperature	Pdh	x,x	kW		
		Tj=operating limit	Pdh	x,x	kW		
		Tj=15°C	Pdh	x,x	kW		
		Average (mandatory)		COPd		x,x	
		Warmer (if designated)		COPd		x,x	
		Colder (if designated)		COPd		x,x	
				COPd		x,x	
Item	symbol	value	unit	Item	symbol	value	unit
Design load		Seasonal efficiency		Bivalent temperature		Operating limit temperature	
cooling	Pdesignc	3,5	kW	cooling	SEER	6,2	°C
heating / Average	Pdesignh	2,5	kW	heating / Average	SCOP/A	4,0	°C
heating / Warmer	Pdesignh	1,4	kW	heating / Warmer	SCOP/W	5,0	°C
heating / Colder	Pdesignh	x,x	kW	heating / Colder	SCOP/C	x,x	°C
Declared capacity* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj		Declared Energy efficiency ratio* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj		Operating limit temperature		heating / Average	
Tj=35°C	Pdc	3,50	kW	Tj=35°C	EERd	3,02	°C
Tj=30°C	Pdc	2,58	kW	Tj=30°C	EERd	4,78	°C
Tj=25°C	Pdc	1,66	kW	Tj=25°C	EERd	7,55	°C
Tj=20°C	Pdc	0,97	kW	Tj=20°C	EERd	10,90	°C
Declared capacity* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Td		Declared Coefficient of performance* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Tj		Annual electricity consumption		cooling	
Tj=-7°C	Pdh	2,30	kW	Tj=-7°C	COPd	2,76	kWh/a
Tj=2°C	Pdh	1,40	kW	Tj=2°C	COPd	3,87	kWh/a
Tj=7°C	Pdh	0,92	kW	Tj=7°C	COPd	5,08	kWh/a
Tj=12°C	Pdh	0,93	kW	Tj=12°C	COPd	6,28	kWh/a
Tj=bivalent temperature	Pdh	2,50	kW	Tj=bivalent temperature	COPd	2,71	kWh/a
Tj=operating limit	Pdh	2,50	kW	Tj=operating limit	COPd	2,71	kWh/a
Declared capacity* for heating / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj		Declared Coefficient of performance* / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj		heating / Average		heating / Warmer	
Tj=2°C	Pdh	1,4	kW	Tj=2°C	COPd	3,9	kWh/a
Tj=7°C	Pdh	0,9	kW	Tj=7°C	COPd	5,1	kWh/a
Tj=12°C	Pdh	0,9	kW	Tj=12°C	COPd	6,2	kWh/a
Tj=bivalent temperature	Pdh	2,5	kW	Tj=bivalent temperature	COPd	2,7	kWh/a
Tj=operating limit	Pdh	2,5	kW	Tj=operating limit	COPd	2,7	kWh/a
Capacity control (indicate one of three options)		Contact details for obtaining more information		christianna.papazahariou@ge.com		Internal communicator - Energy & environment regulations expert	
fixed				LG Electronics		Paris Nord II – 117 avenue des Nations	
staged				BP 59372 Villepinte – 95942 Roissy CDG Cedex		chris.papazahariou@ge.com	
variable				Tel. +33 1 49 89 57 41, +33 6 83 077 455			