




BDO H₂O




[A] attacco standard
standard connection
raccord standard
standard Anschluss
conexión estándar



[B] attacco speciale
special connection
raccord spéciale
speziell Anschluss
conexión especial



[B5O] attacco interasse 5 cm
pipe centres 5 cm
raccords 5 cm
5 cm Achsabstand Anschluss
conexión entre ejes: 5 cm.



P* 122/124

A* cm	inches	B* cm	inches	L* cm	inches	art*	L*	BTU Δt 50°	watt Δt 50°
39.2	15.4	120	47.2	116	45.7	HB20000S039120B	4.4	1 642	481
39.2	15.4	140	55.1	136	53.5	HB20000S039140B	5.0	1 916	561
39.2	15.4	160	63.0	156	61.4	HB20000S039160B	5.6	2 187	641
58.4	23.0	120	47.2	116	45.7	HB20000S058120B	6.2	2 297	673
58.4	23.0	140	55.1	136	53.5	HB20000S058140B	7.0	2 681	785
58.4	23.0	160	63.0	156	61.4	HB20000S058160B	7.8	3 064	898

A* = altezza / height / hauteur / Höhe / alto
I* = interasse / pipe centres / distance entre depart et retour / Achsabstand / distancia entre las conexiones
L* = contenuto acqua / content / volume / Inhalt / volumen

art* = articolo / model / modèle / Artikel / artículo
P* = pagina / page / page / Seite / página

Kcal = Watt x 0.860
BTU = Watt x 3.413

Watt Δt 60° = Watt Δt 50° x 1.255
Watt Δt 40° = Watt Δt 50° x 0.758
Watt Δt 30° = Watt Δt 50° x 0.530
Watt Δt 20° = Watt Δt 50° x 0.320

p max = 10.0 bar

Colori/ colours / couleurs / Farbe / colores

[BIAN] B standard
 T + 10%
 S + 20%
[RAL] S + 20%
 RAL non inclusi in tabella
 special Ral colours
 couleurs Ral spéciales
 RAL Farbe nicht in der Tabelle inbegriffen
 colores RAL especiales

Ulteriori dettagli
Further details
Ultérieures détails
Weitere Einzelheiten
Otros detalles

P* 120

